

93-856 High Visibility Nitrile Exam Glove with Extended Cuff



High visibility color, for protection that you can see

- High visibility orange coloring
- Works exceptionally well in oily environments
- Extended cuff for added protection of wrist and forearm



Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Machinery and Equipment
- Mining
- Oil and gas
- Healthcare

Recommended For

- Inspection, selecting, checking
 parts
- Assembly and inspection of components
- Equipment repair and maintenance
- General Purpose Auto Aftermarket
- Sample taking and processing
- Administering drugs
- Raw material sample collection
- Picking parts and accessories
- Inspection of primary product
- Product inspection
- Vehicle maintenance
- Handling of tools
- Extra protection over the wrist and arm
- Protection from Type I latex allergy in HCW's or patients







93-856 High Visibility Nitrile Exam Glove with **Extended Cuff**

TECHNICAL DATA SHEET

PRODUCT INFORMATION

	93-856		
Material	Nitrile		
Color	Orange		
Glove Design	Chlorinated, Powder-Free, Textured Fingers		
Cuff	Beaded		
Manufacturing/QMS Audit Standards	ISO 13485:2003		
Regulatory/Standards Compliance	Category III, EN 374:2003, EN 374:2003, EN ISO 374-1:2016, EN 420:2003 + A1:2009, EN ISO 374- 5:2016, European Directive 89/686/EEC, FDA21 CFR 177-2600		
Packaging	100 gloves per dispenser 10 dispensers per case 1000 gloves per case		
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition		
Country of Origin	Malaysia		
User Needs Segment	High Risk		
Available sizes	S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10), XXL (10.5 - 11)		

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	270 / 10.6		ASTM D3767,EN420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/inches)	0.13 / 5.1		ASTM D3767,EN420
Finger Thickness (mm/inches)	0.20 / 7.9		ASTM D3767,EN420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥28	≥21	ASTM D412
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥9	≥10	EN 455-2

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: ± 32 (0) 2 528 74 00 F: ± 32 (0) 2 528 74 01

Asia Pacific Region

Asia Pacific Region Ansell Global Trading Center (Malaysia) Sdn Bhd Prima 6, Prima Avenue Block 3512, Jalan Teknokrat 6 63000 Cyberjaya Selangor, Malaysia T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC 111 Wood Avenue South, Suite 210 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Carbbean Region Ansell Commercial Mexico S.A. de C.V. Blvd. Bernardo Quintana No. 7001-C,

Biva. Bernardo Guintana No. /C G7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Gueretaro, Gro. Mexico T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited Level 3,678 Victoria Street, Richmond, Vic, 3121 Australia T: +61 1800 337 041 F: +61 1800 803 578

Russia

Russia Ahcenn PYC 123610 Poccnr, Mockba Kpachonpechehckar Ha6. 12, n.3, op. 1304A Ten. +7 495 258 13 16

Performance Standards and Regulatory Compliance



Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking [©] 2019 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

