TRYON

STYLE AND PERFORMANCE

Ultra wrap-around fit, sporty design, co-injected temples with 160°FLEX technology, adjustable non-slip bridge, PLATINUM® coating. TRYON is the perfect combination of style, innovation and absolute protection.







TRYOPSI • Clear



TRYOPSF • Smoke



TRYOCSP • CSP



TRYOFLASH • Blue Flash



RUSHKITS (optional) Strap only



- WRAP-AROUND FRAME
- + ♦ PLATINUM® COATING (→ P)
 EXCEPT FLASH VERSION
- + CO-INJECTED PC/TPR TEMPLES
- **+ NON-SLIP ADJUSTABLE BRIDGE**
- + I60°FLEX TEMPLES



TRYON

STYLE AND PERFORMANCE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
TRYON	Clear	TRYOPSI	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/⁺₽
	Smoke	TRYOPSF	13	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/⁺₽
	⊘ ∠ CSP	TRYOCSP	I1	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/⁺₽
	Blue flash	TRYOFLASH	12	AS/NZS 1337.1.2010	Hard Coat
	Strap only (optional)	RUSHKITS	-	-	-

LENS MARKING

- → Platinum is a permanent coating applied on both sides of the lens that gives a high resistance to scratching (1.4 cd / m²) and to the most aggressive chemicals and delays the onset of fogging for two minutes, as per the testing requirements of EN166.
- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' signifies that the product has been approved for the use both outdoors and indoors, and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.

Ocular lens category:

- **O.** Range of luminous transmittance 80–100% (Clear).
- 1. Range of luminous transmittance 43-88% (CSP).
- 2. Range of luminous transmittance 18-43% (Flash).
- 3. Range of luminous transmittance 8-18% (Smoke).

TECHNOLOGIES

6CSP

This innovative coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

CSP is also combined with the exclusive PLATINUM® coating that effectively combats fogging.

♦PL\TINUM

The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and effectively delays the appearance of fogging.

LENSES

- 2mm polycarbonate
- Platinum anti-fog/anti-scratch coating on both sides of lens:
 Clear, CSP and Smoke
- · Hard coating on Blue Flash lens
- 100% UV 385 Clear
- 100% UV 400 Smoke, CSP and Blue Flash

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS				
LENSES	PC - 2,2 mm - Curve 8			
FRAME	-			
TEMPLES	PC + TPR			
STRAP	Nylon/15mm/Adjustable			
SPARE LENSES	No			

21/05/2018



Bollé Australia Pty Ltd 32–40 Fairchild Street Heatherton VIC 3202 T: 1300 138 098 E: safety@bolle.com.au NEW ZEALAND: T.: 0800 2655 369 E: bolle@bolle.co.nz



