

AT 65-393

240MM TAN PULL ON RIGGERS BOOT



by Honeywell



STYLE SPECIFICATIONS

DESCRIPTION:

Caustic & water resistant full grain leather steel toe safety rigger's boot

Colour: Tan

Sizes: 5 - 14, 6½ - 12½

Standards:

AS/NZS 2210.3:2009

EN ISO 20345:2011, ASTM F2413-11

Application: Agriculture / Building & Construction / Mining & Quarrying / Chemical / Oil & Gas

FEATURES:

- Caustic & water resistant full grain leather.
- SAFETYcell® integrated TPU shell for enhanced abrasion & cut resistance.
- Heavy duty Kevlar® stitching across all critical wear seams.
- COMFORTcushion® Impact Absorption System with PORON1 protects the heel and ball of the foot.
- NATUREform® steel toe cap with a wide profile for greater comfort.
- NANOlite® footbed with a gently raised surface to help reduce fatigue
- Internal PORON® XRD metatarsal guard.
- Excellent slip resistant sole; SRC slip resistant classification. Anti-static.
- AT's dual density PU/Rubber sole with lightweight shock absorbing PU midsole & hardwearing rubber outsole for superior durability. Resistant to 300 °C surface contact.
- Sole resistant to mineral & organic oils & acids. Cut, split and crack resistant.

COMFORT TECHNOLOGY



COMFORTcushion
Impact
Absorption



NATUREform
wide profile Type
1 safety toe cap



Water Resistant
Leather



Steel Safety
Toe Cap



NANOlite
footbed



Metatarsal
protection



SAFETYcell
protection

SOLING TECHNOLOGY



300°C
Heat Resistant
sole (572° F)



Abrasion
Resistant sole



Cut Resistant
sole



Slip Resistant
sole



Sole resistant to
mineral oils
and acids



Sole resistant to
organic oils
and fats



Antistatic
discharges static
build-up

OLIVER FOOTWEAR

Prest Street Ballarat
Victoria 3350 Australia

Tel: 1300 1 BOOTS (26687)
Fax: (03) 53 200 299

Email: info@oliver.com.au
www.oliver.com.au



[Facebook.com/oliversafetyfootwear](https://www.facebook.com/oliversafetyfootwear)



[@oliverfootwear](https://www.instagram.com/oliverfootwear)

Honeywell